		4			3	\downarrow		2			1						
<u>'</u> [DISCLOSED IN CO	DNFIDENCE AND	NOT TO BE REPRO	TTY OF CELESTRA, IS DUCED, USED OR		CELEST CAT.No		IRE SIZE FLEX	BOLT SIZE	B C	D 04 ±0.015	G ±0.02	H ±0.01	'			
D	DISLOSED EXCE	PT FOR WHICH I	FURNISHED.			LB30380		150 Navy 2/0 Weld 325/24 = 131 kcmi 133/.0316 259/.0227 427/.0177	d I	1.63 0.9		1.00	0.57	D			
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE																
		ON (PRE OTH	CODE WIRES AND -FIX CAT.NO.WITH ERWISE SPECIFII	H "L" HAS NOT PEEP ED IN THE SUFFIX O	CABLES. HOLE UNLESS		B V										
	WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: FILECTOR TIN DI ATE UNI FOR OTHERWISE								Ċ)							
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry H											С					
\rightarrow	INSTALLATION GUIDE DIE CODE = 50 DIE COLOR = Orange						Wire inspection hole —BOLT SIZE										
В	CUL US LISTED WIRE CONNECTORS						Color coded barrel markings										
-														_			
						HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.											
A							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
[7 0					MATERIAL HIGH-COND WROUGHT	COPPER LB3	03801A	LINIT	NTS	RID ANGLE PI	PROJECTION				
[REV DATE	DWN 4	CHK	DESCRI	PTION 3	ECN	ELECTRO TII	N PLATE	186-cp470	1 0	INCH 1	9 -	7	i			