			4		1		3	$\forall$	7		2		ı		1				
	THEIN	NEORMATION	ON THIS DRA	WING IS THE	PROERTY OF	CELESTRA, IS	<u> </u>	1	/ CELESTRA		IRE SIZE	BOLT	l B	С	D	G	Н	ı	
	DISCL	OSED IN CON	NFIDENCE AND FOR WHICH	NOT TO BE					CELESTRA CAT.NO	CODE	FLEX	SIZE	MIN	_	±0.015		±0.01		
D	DISLO	SED EXCEPT	FOR WHICH	FURINISHED.			J		LB305601AP 250	3/0 AWG	150 Navy 2/0 Weld 325/24 = 131 kcmi 133/.0316 259/.0227 427/.0177		1.78	0.96	0.13	1.00	0.58	D	
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																		
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□																		
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	М	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry									
											′ → H -								
	D	INSTALLATION GUIDE DIE CODE = 50 DIE COLOR = Orange								—Wire inspection hole —BOLT SIZE									
В			C U		RoH 2002/95/	S					Color co	ded bar	rel ma	ırkings	Die C	olor		В	
			2MV 0/2778															_	
										HU\ www.huyac		ELES 76. Hua Panyu [	ncun	Rd. Zł	nongci	ın Tow	_		
Α									TI	WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00	0   23-Aug-25   Ruby Feng   Sinia Qiu   Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECT WROUGHT COPPER LB305601AP-250 NTS							ROJECTION			
ı	REV		DWN	СНК		DESCR			ECN FI	VISH ELECTRO TIN	DWG NO	186-cp47		NIIT	ICH -	<b>\Phi</b> E	$\exists$		
		•	4				3	4		2			İ		1				
								- 1											