	_								1												
			4				3		\overline{V}			2				1					
'			I ON THIS DRA NFIDENCE AND			CELESTRA, IS D, USED OR			CELEST CAT.N		CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D +0.015	G ±0.02	H ±0.01	,		
	DISLO	OSED EXCEPT	FOR WHICH	FURNISHED.					LB30143								1				
									251		3/0 AWG	450/24 3/0 Weld	1/4	1.53	1.06	0.14	0.75	0.64			
_																					
D		NOTE:	1 ΔΙΙ	DIMENSION	IS ADE IN I	NCHES UNLES	S OTHERW	/ISE											D		
	'	NOTE.		CIFIED.	NO AILL IIV I	INOTILO UNLLO	3 OTTLKW	IOL													
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE								B →											
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																			
_	┨																				
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.								S S S S S S S S S S S S S S S S S S S											
			WITI	H "P".																	
	N	MATERIAL:	HIGI	H CONDUCT	TIVITY WRO	DUGHT COPPE															
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.						Beveled wire entry													
				FIX CAT.NC				** H 1**													
		INSTALLATION GUIDE									Wire inspection hole										
_											-BOLT SIZE										
		DIE CODE = 50 DIE COLOR = Orange																			
		- C																			
																Pio C	`olor				
В						/		□ G □ □										В			
Ь		c(VL)us RoHs.								Color coded barrel markings—											
		2002/95/eC																			
			WIRE CONN ZMVV/2/7/8																		
	1																		_		
													CFI FS	STRA	CO	RPO	RATIO	ON			
									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.												
	-														anyu Dist. Guangzhou 511495.						
Α										TITLE WIRE CONNECTORS AND SOLDERING									Α		
											LUGS FOR CODE AND FLEX CABLE										
		00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.								MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION											
	00 REV	23-Aug-25 DATE	DWN	CHK			iras Spec. Ir ———— IPTION	mualeu.	ECN	FINISH	WROUGHT O	DWG NO	434AP-25		INIIT	TS	6	\Rightarrow			
1	IVE V	DAIL	4	CHIN	ı	DLJCK	3				electro tin	I PLATE	186-cp47	ا _ا ا	IN	ICH 1	Ψ ,		l		
	_		4				3		4		۷					ı					