| THE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR CAT.NO CODE FL | BOLT B C D G H EX SIZE MIN ±0.04 ±0.015 ±0.02 ±0.01 |
|---|--|
| DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR | EX SIZE MIN ±0.04 ±0.015 ±0.02 ±0.01 |
| DICLOSED EVOLDT FOR WILLIGHT CAT.NO CODE FL | |
| DISLOSED EXCEPT FOR WHICH FURNISHED. | |
| | 182 kcmil 1/4 1.64 1.02 0.14 1.00 0.63 |
| | .0154 |
| D | D |
| NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE | |
| SPECIFIED. | |
| 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE | |
| LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. | B |
| ON CODE WIRES AND FLEX/24 STRAINDED CABLES. | |
| PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS | D D |
| OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". | - So F |
| MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER | |
| | |
| C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. Beveled wire entry | [C |
| | H |
| | |
| | |
| Wire inspection | on hole |
| INSTALLATION GUIDE DIE CODE = 54 BOI | LT SIZE |
| DIE COLOR = Purple | |
| | +¢ |
| | |
| | Die Çolor |
| | В |
| 2002/95/EC | Color coded barrel markings— |
| LISTED | |
| WIRE CONNECTORS ZMVV(2)7/8 E513913 | |
| | |
| | |
| | CELESTRA CORPORATION |
| HUYA® | 76. Huancun Rd. Zhongcun Town. |
| www.huyaco.com | Panyu Dist. Guangzhou 511495. |
| | |
| WIRE CON | NECTORS AND SOLDERING |
| LUGS FOR | CODE AND FLEX CABLE |
| 00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed. MATERIAL HIGH-CONDUCTIVITY PROUGHT COPPER | RT. NO. DB401401A-260 SCALE THRID ANGLE PROJECTION NTS |
| 3 7 3 WKOOGHI COFFER | WG. NO. 186-cp4729 UNIT INCH |
| 4 1 2 | 1 1 |
| | |