													_					
			4				3		∇		2				1			
•			ON THIS DRA NFIDENCE AN			F CELESTRA, IS D, USED OR			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	
	DISLOS	SED EXCEPT	FOR WHICH	FURNISHED.					DB403801A-2		550/24 4/0 Weld		1.82	1.19	0.16	1.00	0.73	
											•	-						
_																		_
D	l N	OTE:	1. ALI	DIMENSION	IS ARE IN I	NCHES UNLES	S OTHERWISE											D
		· - ·		CIFIED.							K	В						
		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE																
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																	
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								D D									
		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
									Beveled wire entry									
С		FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							— H № C									С
			SUF	FIX CAT.NO).WITH "SP	FOR SILVER.												
										Wire	inspection hole							
_										BOLT SIZE								
\rightarrow	INSTALLATION GUIDE DIE CODE = 54																	\leftarrow
	DIE COLOR = Purple																	
		Die colo																
										,					/-			
В									Color coded barrel markings—									В
		С		RoHS 2002/95/EC	1													
		L	ISTED RE CONNECTORS		l													
		ZM	VV/2/7/8.E513913															
	1																	
												FIFS	TRΔ	COI	RP∩I	RATIC)N	
									HUYA® 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
Α									TI	TITLE WIRE CONNECTORS AND SOLDERING								
									+	LUGS FOR CODE AND FLEX CABLE								
	00	00 15-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							М	ATERIAL HIGH-COND WROUGHT	UCTIVITY PRT. NO.	801A-251	SC	CALE N		RID ANGLE PRO	DJECTION	
	REV	DATE	DWN	СНК			IPTION		ECN FI	NISH ELECTRO TII	DWG NO	186-cp473	6 UI	NIT	CH -	\bigcirc \in	\exists	
			4				3		<u> </u>	2	1	•	 		1			
					ı								'					