	,							1										
		4			3				2									
ļ					PROERTY OF C REPRODUCED,			CELES			RE SIZE	BOLT	В	С	D	G	Н	
			T FOR WHICH		REPRODUCED,	USED OR		CAT		CODE	FLEX	SIZE	MIN		0.015		±0.01	
								DB40120	1A-251	4/0 AWG	550/24 4/0 Weld	1/2	2.09	1.19	0.16	1.00	0.73	ĺ
D																		D
	N	IOTE:		DIMENSION CIFIED.	S ARE IN INC	CHES UNLESS	S OTHERWISE											
						SEDIES OF C	AT NO S ABE	B → I										
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUIFELY OF THE CAT.NO.							- S * * D									
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	M	MATERIAL:	HIG	H CONDUCT	IVITY WROU	GHT COPPER	₹		Beveled wire entry————————————————————————————————————									
С	F	INISH:	ELE	CTOR-TIN P	LATE UNLES	S OTHERWIS	SE											
C		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							——————————————————————————————————————									
			001	TIX OAT.NO	.wiiii Oi i	OIT OILVEIT.												
									Wire inspection hole									
_		JOTALI ATI						BOLT SIZE										
	INSTALLATION GUIDE DIE CODE = 54																	
	D	DIE COLOR = Purple																
		Die Çalor																
																	В	
В			ر <b>ا</b> )	) IIc	Polis			Color coded barrel markings—										
				りい	2002/95/EC	ľ												
			LIS <sup>1</sup>			•												
			ZMVV/2/7/8	I.E513913														
_	-																	
									Ι_		<b>-</b> A - 1		TD 4	000		ATIC	\ <u>\</u>	
									╢╟	<b>YUH</b>		<b>CELES</b> 76. Hua						
										ww.huyac		Panyu [					١.	
Α									WIRE CONNECTORS AND SOLDERING									Α
		LUGS FOR CODE AND FLEX C																
																	ROJECTION	
		23-Aug-25     Ruby Feng     Sinia Qiu     Celestra Standards Spec. Initialed.       DATE     DWN     CHK     DESCRIPTION					WROUGHT COPPER DB401201A-251						TS THRID ANGLE PROJECTION					
ı	REV	DATE	DWN	CHK	1	DESCR		ECN	I-IIVISI	ELECTRO TIN	PLATE DWG. NO.	186-cp47	37	INC	H   4	¥ _	7	1
			4				3	4		2					1			