								I									
		4			3				2								
ļ					PROERTY OF C REPRODUCED,				.ESTRA		RE SIZE	BOLT	В	С	D		┤ '
			T FOR WHICH		REPRODUCED,	USED OR			AT.NO	CODE	FLEX	SIZE	MIN		0.015		
							_	DB401	241A-261	4/0 AWG	550/24 4/0 Weld	1/2	2.33	1.14	0.15	1.25 0.	1
_																	
D	l N	OTE:	1. ALL	DIMENSION	S ARE IN INC	CHES UNLES	S OTHERWISE										D
	SPECIFIED.											⊸——E	}				
	<ol> <li>ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE</li> </ol>																
		ON CODE WIRES AND FLEX/24 STRANDED CABLES.															
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER								Beveled wire entry								
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.								H - H								
					.WITH "SP" F												
										∕—Wire i	nspection hole						
									BOLT SIZE								
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 54																$\leftarrow$
	D	DIE COLOR = Purple															
		□ G □ Die ¢olor															
D					./	,			Color coded barrel markings								
В			c(N	L)us	RoHS	5,		Color coded barrel markings—									
			LIS	TED	2002/95/EC												
			WIRE CON ZMVV/2/7/8														
																	_
		<u> </u>	I						<u> </u>								$\exists$
									-	HUY				CORI Rd. Zho			
	<u> </u>			-						www.huyaco.com Panyu Dist.							
Α		WIRE CONNECTORS AND SOLDER LUGS FOR CODE AND FLEX CABLE							SOLI	DLDERING							
	00	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PE WROUGHT COPPER DB401241A-261 NTS							ANGLE PROJEC	TON		
1	REV		DWN	СНК		DESCR		EC	N FINISH		DWG NO	186-cp47		INCH	$\dashv$ (4		F
			4				3	<u> </u>	•	2	•		İ		1		<b>-</b>
								I									