							1										
		4				3	4	7		2				1			
ı				PROERTY OF CELES [®] REPRODUCED, USED				CELESTRA	-	IRE SIZE	BOLT	В	С	D	G	Н	1 '
		XCEPT FOR WHICH		REPRODUCED, USED	OR		-	CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
								LB403801AP-	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmi		1.86	1.06	0.14	1.00	0.64	
								250		703/.0154							1
D																	D
	NOTE:			IS ARE IN INCHES													
	SPECIFIED.																
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 							⇔——B——⇔								
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.															
		WITH "P". TERIAL: HIGH CONDUCTIVITY WROUGHT COPPER															
	MATER																
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							Beveled wire entry									
				.WITH "SP" FOR S				Beve	ica wiic chi	y_ → H ←							
									—Wire inspection hole								
\rightarrow	INSTALLATION GUIDE						/-BOLT SIZE										
		DE = 54 LOR = Purple						/		BOLI SIZE							7
	5.2 00									E C							
								X		ž							
_				./					A	-G				Die C	olor		_
В							/=			В							
	Color coded bar							rel ma	el markings <i>—</i>								
			TED NNECTORS														
		ZMVV/2/	7/8.E513913														
	-																l —
								1 1									
									HUY		ELES						
									www.huyad		76. Hua Panyu F						
Α																A	
									WIKE CONNECTORS AND SOLDERING								^
								LUGS FOR CODE AND FLEX CABLE									
	00 23-Au	g-25 Ruby Fen	g Sinia Qiu	Celestr	ds Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER LB403801AP-250 NTS								ROJECTION		
	REV DA		CHK	[DESCRIP	PTION		ECN FIN	IISH ELECTRO TII	51116 116	86-cp476		NIIT	ICH I	(1 .
		4		1		3	\triangle	\	2		•			1	-		'
		-		I			4		_			ı					