		4		1		3		+	2			1		1			
		THE INFORMATION ON THIS DRAWING IS THE PROE DISCLOSED IN CONFIDENCE AND NOT TO BE REPRO						CELESTRA	WIRE	SIZE	BOLT	A	В	С	R	ID	,
	DISLOSED EXCEP			KEPRODUCEL), 03ED OR			CAT.NO DA2512-260	CODE 250 kcmil	FLEX 250 Navy 262.6	SIZE 1/2	±0.06	MIN 1.08	±0.04	1.41	±0.01	
								DA2512-200	250 KCMIII	kcmil	1/2	2.49	1.06	1.11	1.41	0.61	
D	NOTE:		DIMENSION CIFIED.	S ARE IN IN	ICHES UNLE	SS OTHERWI	ISE	Color coded marking Bolt Size									D
		LIST ON (ED BY "UND CODE WIRES	ERWRITER S AND FLEX	I SERIES OF RS INC." AND K/24 STRAND HAS NOT PEE	ISE	Doil Size										
		OTH				OF THE CAT											
	MATERIAL:	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER B															
С	FINISH:	SPE	CIFED PLAT	E PER MIL	SS OTHERW - T -16366. FOR SILVER			Joa	/	A	-						С
-	INSTALLATION GUIDE DIE CODE = 62 DIE COLOR = Yellow R Inspection Hole																
В	c (LISTE	_	A N	IEB\$	ς3 _Β	ŠHS (E	<u>□</u>	Bevele	d entry			E				В
_	WIRE CON	NECTOR															
А									HUY www.huyaco	A	ELES 76. Hua Panyu [ancun	Rd. Zh	ongci	ın Tow	'n.	
								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
		Ruby Feng		Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDU WROUGHT CO	DPPER DA25	12-260		CALE N7		RID ANGLE PI	ROJECTION	
1	REV DATE	DWN	CHK	1	DESC	RIPTION		ECN	ELECTRO TIN I	PLATE DWG. NO.	86-cp04	77 ^U	NIT IN	CH -	(
		4				3		4	2					1			