									1									
		4 THE INFORMATION ON THIS DRAWING IS THE PROERTY			3			7	2				1			.		
•			ON THIS DRA NFIDENCE ANI						CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	·
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					LB401434AF							<u> </u>		
									261	4/0 AWG	550/24 4/0 Weld	1/4	1.39	1.14	0.15	0.75	0.71	
_																		_
D	l N	IOTE:	1 ΔΙΙ	DIMENSION	JS ARE IN IN	NCHES UNLESS	CTHERWISE											D
	"	IOTE.		CIFIED.	NO ARE IN II	NOTILS OINLES	OTTLKWISE											
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 							>B									
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.								<i>†</i> I	D D								
		WITH "P".																
	M	MATERIAL:	HIGI	H CONDUC	TIVITY WRC	UGHT COPPER												
С	C FINISH: ELECTOR-TIN PLATE UNLESS OTHER' SPECIFED PLATE PER MIL - T -16366.						E	Beveled wire entry									С	
						FOR SILVER.		II										
										∕──Wire inspection hole								
\rightarrow		INSTALLATION GUIDE								BOLT SIZE								
		DIE CODE = 54 DIE COLOR = Purple																
															Diac	alar		
В		⊸-G-⊸									В							
Ь									Color coded barrel markings—								ט	
	C US ROHS																	
		WIE ZM	LISTED RE CONNECTORS VV/2/7/8.E513813		•													
	1																	
												FLFS	TRA	CO	RPO	RATIO	NC	
										HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.								
										www.huyad	co.com	Panyu Dist. Guangzhou 511495.						
Α										TITLE WIRE CONNECTORS AND SOLDERING								Α
										LUGS FOR CODE AND FLEX CABLE								
	00) 28-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initiale					 d.	М	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PRO. WROUGHT COPPER LB401434AP-261 NTS							ROJECTION		
	REV		DWN	CHK		DESCR			ECN FI	VISH ELECTRO TI	DWG NO	86-cp47		NIIT	ICH	(E	\exists	
		l	4	l			3	/		2				111	1			'
			-		I		-	_	Γ	_			1					