		4				3	7	\downarrow	2					1				
1	DISCLO	SED IN CON	ON THIS DR/ IFIDENCE AN FOR WHICH	d not to be i	PROERTY OF CI REPRODUCED, U	ELESTRA, IS JSED OR			CELESTR CAT.NO		VIRE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLOSI	ED EXCEPT	FOR WHICH	FORNISHED.					LB403801A 261	AP- 4/0 AWG	550/24 4/0 Weld	3/8	1.83	1.14	0.15	1.00	0.71	
D										·						•		D
	NO	DTE:	1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.															
			LIST	FED BY "UNE	3,WP AND J S DERWRITERS S AND FLEX/2	INC." AND "	CSA" FOR US											_
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								D D								
		MATERIAL:HIGH CONDUCTIVITY WROUGHT COPPERFINISH:ELECTOR-TIN PLATE UNLESS OTHERWISESPECIFED PLATE PER MIL - T -16366.SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry								
С	FIN																	С
									Wire inspection hole									
\rightarrow	INSTALLATION GUIDE DIE CODE = 54																\leftarrow	
	DIE COLOR = Purple																	
В			c (U	Dus	RoHS	1			Color coded barrel markings									В
																		—
										HU					CORPORATI			
										www.huya		Panyu Dist. Guangzhou 5			11495.			
A								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									A	
			Ruby Feng		Ce		ards Spec. Init	tialed.			COPPER LB403	301AP-26	61		ts I		ROJECTION	
	REV	DATE	DWN 4	СНК		DESCR	RIPTION 3	,	ECN	ELECTRO	TIN PLATE	186-cp47	78 ¹	init IN	існ ¹	Ψt		
			4		I		3	Z	\downarrow	Z			I		I			