		4 3			$\bigvee$	√ 2				1								
ı						CELESTRA, IS			CELESTRA		RE SIZE	BOLT	В	С	D	G	Н	] '
			FOR WHICH	D NOT TO BE I FURNISHED.	REPRODUCEI	J, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
_							_	D	B253801A-2		4/0 Weld 550/24 = 222 kcmil 133/.0399 259/.0286 637/.018	3/8	2.80	1.25	0.15	1.00	0.75	
D	NO	OTE:		DIMENSION CIFIED.	IS ARE IN II	NCHES UNLESS	S OTHERWISE											D
			LIST	red by "Und	PERWRITE	J SERIES OF CARS INC." AND "C X/24 STRANDE		>──B										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	М	ATERIAL:	HIG	H CONDUCT	TIVITY WRC	UGHT COPPER	₹		-80									
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry H									
	INSTALLATION GUIDE DIE CODE = 62 DIE COLOR = Yellow								-Wire inspection hole -BOLT SIZE									
В	CUL US ROHS								Color coded barrel markings									
_			V/22/7/8_E513813															_
		_						HUYA®  CELESTRA CORPORATION  76. Huancun Rd. Zhongcun Town.  Panyu Dist. Guangzhou 511495.										
А									TI	WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	00	29-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECT WROUGHT COPPER DB253801A-241 NTS							ROJECTION		
1	REV	DATE	DWN	CHK		DESCR	PTION		ECN FII	NISH ELECTRO TIN	DWG NO	186-cp478		NIT	iCH -	<b>+</b> E		
			4				3	4		2					1			