									1									
			4				3	7	7		2	_			1			,
•			I ON THIS DRA NFIDENCE ANI			CELESTRA, IS D, USED OR			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	•
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					WP253801A	_					1			
									177	250 kcmil	250 Navy	3/8	1.82	1.20	0.16	1.00	0.72	
_																		
D	l N	IOTE:	1 ΔΙΙ	DIMENSION	JS ARE IN IN	NCHES UNLES	S OTHERWISE											D
		IOTE.		CIFIED.	NO AILE IIV II	VOLIES OIVEES	OTTLKWISE											
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE							P B P									
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
										S D								
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.																
	WITH "P".																	
	M	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	F	INISH:		CTOR-TIN F		SS OTHERWIS	E		Beve	eled wire entr	y H							С
						FOR SILVER.		** 11 ***										
										Wire inspection hole								
\rightarrow		INSTALLATION GUIDE								BOLT SIZE								
		DIE CODE = 62 DIE COLOR = Yellow																
		()																
															Dia	color		
В		⊢-G-⊢																
Ь								Color coded barrel markings—							В			
	C US ROHS																	
		WIF	LISTED RE CONNECTORS REVIZITIBLES 13813		•													
	1																	
												ELFS	STRA	CO	RPO	RATIO	ON	
										HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.								
										www.huyaco.com Panyu Dist. Guangzhou 511495.								
Α									WIRE CONNECTORS AND SOLDERING								Α	
									_	LUGS FOR CODE AND FLEX CABLE								
	00	28-Oct-25	5 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PR							ROJECTION	NC	
	REV		DWN	CHK		DESCR	·		ECN FI	WROUGHT (DWG NO	186-cp47		INIIT	ICH	(1)	\exists	
			4		l	220011	3	/		2	YFLAIE	. 30 op+1	 	111	1	Т		
			т		I		J	_	\vdash	_			I		'			