			4		1		3	_	<u></u>		2		1		1			
	THEIN	NFORMATION	ON THIS DRA	WING IS THE	PROERTY OF	CELESTRA, IS	3	\	CELESTRA	_	IRE SIZE	BOLT	В	С	Тр	G	Н	
	DISCL	OSED IN CON	NFIDENCE AND T FOR WHICH	NOT TO BE					CAT.NO	CODE	FLEX	SIZE	MIN	_		±0.02	±0.01	
							_		WP253801A- 177	250 kcmil	250 Navy	3/8	1.82	1.20	0.16	1.00	0.72	
															1	1	1	
D																		D
	N	IOTE:		DIMENSION CIFIED.	NS ARE IN IN	ICHES UNLESS	OTHERWISE											
						SERIES OF C		□ B										
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	1	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								-9° *								
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE							Beveled wire entry									С	
		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							->									
		INSTALLATION GUIDE								Wire inspection hole								
\rightarrow										BOLT SIZE								
		DIE CODE = 62 DIE COLOR = Yellow																7
									1		\$\frac{1}{2} \frac{1}{2} \frac{1}{2} \frac{1}{2} \frac{1}{2} \frac							
											-G>				Die C	Color		
В										/=			В					
	CUL) US ROHS							Color coded barrel markings—										
			LIST	TED														
			WIRE CONN ZMVV/2/7/8															
																		_
		ı	I		I				1 1									
										HU)		ELES						
								76. Huancun Rd. Zhongcun Town. www.huyaco.com Panyu Dist. Guangzhou 511495.										
Α								TITLE WIRE CONNECTORS AND SOLDERING								Α		
									LUGS FOR CODE AND FLEX CABLE									
										MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION								
		23-Aug-25			(rds Spec. Initialed	l		WROUGHT (COPPER WP253	801A-17	7		TS I''	RID ANGLE P	ROJECTION	
ı	REV	DATE	DWN	CHK		DESCRI		,	ECN FIN	ELECTRO TIN	I PLATE	186-cp47	96	IN IN	ICH	Ψ -		
			4				3	_		2					1			