		4		3			2			1								
•			ON THIS DRA NFIDENCE AN			F CELESTRA, IS D, USED OR			CELESTRA CAT.NO	CODE	/IRE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					LB251243AF	,	550/24 = 222 kcmi	ı						l
									250	250 kcmil	4/0 Weld	1/2	3.00	1.17	0.14	1.75	0.70	
_																		_
D	<sub>N</sub>	IOTE:	1 11	DIMENSION	IC ADE IN I	NCHES UNLES	OTHEDWISE											D
		IOTE.		CIFIED.	NO AILL IIV I	NOTIES ONLES	OTTILITYIIGL											
		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE										——Е	3	~				
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	ł	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.																l —
		WITH "P".																
	M	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.					E		Beveled wire entry									С	
						FOR SILVER.		——————————————————————————————————————										
										Wire inspection hole								
$\rightarrow$		INSTALLATION GUIDE								BOLT SIZE								
	DIE CODE = 62 DIE COLOR = Yellow																	7
		( )																
															Dia	color		
В		G—G Color coded ba								Join Colon					В			
Ь									Color coded barrel markings—									
		WIR ZM	.ISTED RE CONNECTORS VV/2/7/8.E513913		,													
	1																	
												ELES	TRA	CO	RPO	RATIO	NC	
										HU		76. Hua	ncun	Rd. Zł	nongci	un Tow		
										www.huyaco.com P		Panyu Dist. Guangzhou 511495.						
Α									WIRE CONNECTORS AND SOLDERING								Α	
									_	LUGS FOR CODE AND FLEX CABLE								
	00	00 15-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECT								ROJECTION	İ
	REV	DATE	DWN	CHK		DESCR			ECN F	NISH ELECTRO TI	DWG NO	43AP-25 186-cp48		INIIT	ICH	<b>(1)</b>	$\exists$	İ
			4	2	<u> </u>	320011	3	/	1	2	IN FLATE	. 30 op 40		111	1	Т		'
			•		I		J	Z	†	_			1		'			