									1				•					\neg
		4			3		7	∇	2					1			.	
•	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE		CELESTRA, IS D, USED OR			CELESTRA CAT.NO	CODE	/IRE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	·
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					LB253801AF	,	550/24 = 222 kcmi							
									260	250 kcmil	4/0 Weld	3/8	1.83	1.10	0.14	1.00	0.68	
_																		_
D	l N	IOTE:	1 ΔΙΙ	DIMENSION	JS ARE IN I	NCHES UNLESS	CTHERWISE											D
	"	IOTE.		CIFIED.	NO ARE IN II	NOTILS UNLLS	OTTIERWISE											
			2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE								В — □ .							
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	ł	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.											—					
		WITH "P".																
	M	MATERIAL:	HIGI	H CONDUCT	TIVITY WRC	UGHT COPPER	1											
С	F	INISH:		ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.						Beveled wire entry								
						FOR SILVER.		71 11 17										
										Wire inspection hole								
\rightarrow		INSTALLATION GUIDE								BOLT SIZE								
	DIE CODE = 62 DIE COLOR = Yellow																	7
															Die C	olor		
В		G—G—⊲ Color coded barrel ı									В							
Ь										Color coded barrel markings—								D
		C US ROHS																
		WIR ZM	LISTED RE CONNECTORS VV/2/7/8.E513813		'													
_	1																	
												ELES	TRA	CO	RPO	RATIO	NC	
										HUY	'A	76. Hua	ncun	Rd. Zł	nongci	un Tow	_	
																ist. Guangzhou 511495.		
Α									TITLE WIRE CONNECTORS AND SOLDERING									Α
									+	LUGS FOR CODE AND FLEX CABLE								
	00	00 29-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION WROUGHT COPPER LB253801AP-260 NTS									
	REV		DWN	CHK		DESCRI			ECN FI	NISH ELECTRO TI	DWG NO	86-cp48		INIIT	ICH	(\exists	
		l	4				3	/		2			- 1		1			
			-		ı		-	_	Τ	_			1					