			4		1		0	_	<u></u>		^		1		4			
	THEIN	VIEODMATION	4	WINC IS THE	DDOEDTY OF	CELESTRA, IS	3		V	_	2		<u> </u>		<u></u>	Ι _		
	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE					CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	±0.015	G ±0.02	+0.01	
	DISLO	DSED EXCEPT	FOR WHICH	FURNISHED.					LB253801AP		262.6 kcmil	3/8	1.82	1.28	0.17	1.00	0.79	
									251									
D																		D
	N	IOTE:		DIMENSION CIFIED.	NS ARE IN I	NCHES UNLES	S OTHERWISE											<b>D</b>
			2. ALL	DA,DB,LA,L	B,WP AND	J SERIES OF C		<del>□</del>   B										
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
_	-	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							Beveled wire entry————————————————————————————————————									С
			SUF	FIX CAT.NC	).WITH "SP'	FOR SILVER.												
								∕—Wire inspection hole										
	1	INSTALLATION GUIDE								BOLT SIZE								
	DIE CODE = 62 DIE COLOR = Yellow																	
		AL OOLON.	- TCHOW						-		₹ + C							
											-G				Die	Color		
В					V	/				<b>⊸</b>								В
٥	Color coded barrel i								rel ma	ırkings	J							
			LIST	TED														
			WIRE CONN ZMVV/2/7/8															
																		_
		I	1	I	I													
										HU1		ELES						
	-								76. Huancun Rd. Zhongcun Town. www.huyaco.com Panyu Dist. Guangzhou 511495.									
Α						_	_	TITLE WIRE CONNECTORS AND SOLDERING								Α		
		23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						LUGS FOR CODE AND FLEX CABLE										
	00						d.	M	MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER LB253801AP-251 NTS							ROJECTION		
	REV		DWN	СНК		DESCR			ECN FI	VISH ELECTRO TIN	DWG NO	186-cp48		NIIT	ICH	<b>+</b> E	$\Rightarrow$	
		I	4	I			3			2			<del> </del>		1	<u>.</u>		
					ı								1					