			4				3	7	∇		2				1			
•	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE		CELESTRA, IS D, USED OR			CELESTR CAT.NO		VIRE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	·
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					LB253801A		250 kcmil 637/2		1.83	1.28	0.18	1.00	0.79	
									263	· ·	Class I, K, M	3/0	1.03	1.20	0.16	1.00	0.79	
Г.																		
D	l N	IOTE:	1. ALL	DIMENSION	NS ARE IN II	NCHES UNLESS	S OTHERWISE											D
				CIFIED.														
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 							B									
	1	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
									Da	والمالية المالية								
С		FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							Beveled wire entry————————————————————————————————————									
			SUF	FIX CAT.NC).WITH "SP"	FOR SILVER.												
										—Wire inspection hole								
_	l .,	INSTALLATION GUIDE								/BOLT SIZE								
	D	IE CODE =	62															
	D	DIE COLOR :	= Yellow						+		\$\frac{1}{8} \cdot							
_						/				<	-G⊳				Die C	olor		_
В	B COlor coded								oded ba	parrel markings					В			
			1103		2002/95/8	:5/												
			WIRE CONN ZMVV/2/7/8															
	1																	
												CELES	STRA	CO	RPO	RATIO	ON	
										HU'	YA	76. Hua	ancun	Rd. Zł	nongci	un Tow	n.	
									www.huyaco.com Panyu Dist. Guangzhou 51149						11495.			
Α										TITLE WIRE CONNECTORS AND SOLDERING A								Α
										LUGS FOR CODE AND FLEX CABLE								
	00	23-Aug-25	ug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTI UROUGHT COPPER LB253801AP-263 NTS								ROJECTION	
	REV	DATE	DWN	CHK		DESCRI	PTION		ECN	FINISH ELECTRO	DWG NO	186-cp48		INIIT	ICH .	(
		•	4				3		1	2			j		1			'
					•				I				•					