			4				3	$\bigvee$			2				1			
ı				WING IS THE D NOT TO BE F		CELESTRA, IS			CELESTRA		RE SIZE	BOLT	В	С	D	G	Н	1 '
			FOR WHICH		REPRODUCE	D, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	-		±0.02	±0.01	1
								DE	3311243A-250	300 kcmil	300 Navy	1/2	3.00	1.19	0.16	1.75	0.72	
D	NC	DTE:		DIMENSION CIFIED.	S ARE IN I	NCHES UNLES	SS OTHERWISE											D
_	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																_	
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER								Beveled wire entry									
С	FIN	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE  SPECIFED PLATE PER MIL - T -16366.  SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
	∕—Wire inspection hole																	
-	DIE	INSTALLATION GUIDE DIE CODE = 66 DIE COLOR = White							BOLT SIZE									
В			C U		<b>PoH</b>	S				∞_		oded bar	rel ma	arkings-	Die Ço	olor		В
																		l
	ļ ,		ı								<u>. I</u>							
										<b>-UY</b> ww.huyac		<b>CELES</b> 76. Hua Panyu [	ncun	Rd. Zh	ongcı	ın Tow		
Α									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									А
	00 2	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				d.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE P WROUGHT COPPER DB311243A-250 NTS							OJECTION				
	REV	DATE	DWN	CHK		DESCI	RIPTION		ECN FINIS		DWG NO	186-cp48	_	INC	_	<b>⊕</b> €		
			4	•			3	4		2					1			
								1										