			4				3		7		2				1			_	
•			ON THIS DRA			CELESTRA, IS D. USED OR			CELESTRA CAT.NO		IRE SIZE	BOLT SIZE	B MIN	C	D	G ±0.02	H	'	
			FOR WHICH						LB311243AP	CODE	FLEX						±0.01		
									250	300 kcmil	300 Navy	1/2	3.00	1.19	0.16	1.75	0.72		
D																		D	
	N	IOTE:		DIMENSION CIFIED.	IS ARE IN I	NCHES UNLESS	OTHERWISE												
		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE							⊱⊸—B—⊸⊣										
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE																	
		ON CODE WIRES AND FLEX/24 STRANDED CABLES.																 	
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.								D D										
		WITH "P".																	
	М	IATERIAL:	HIG	H CONDUC	TIVITY WRO	OUGHT COPPER													
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE							Beveled wire entry										
O		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry————————————————————————————————————									
								—Wire inspection hole											
_		INSTALLATION GUIDE								BOLT SIZE									
	D	DIE CODE = 66																	
	D	DIE COLOR = White																	
										—	-G⇒				Die C	olor			
В	Color coded barrel markings—											В							
		C(UL)US ROHS																	
		L	.ISTED	2002/95/EC	l														
		VIR ZM	RE CONNECTORS VV/2/7/8.E513813																
																		_	
		I	I																
									HU)		ELES								
A										76. Huancun Rd. Zhongcun Town. www.huyaco.com Panyu Dist. Guangzhou 511495.							n.		
																		Α	
, \										WIRE CONNECTORS AND SOLDERING									
										LUGS FOR CODE AND FLEX CABLE									
	00	0 14-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJ. WROUGHT COPPER LB311243AP-250 NTS							ROJECTION			
1	REV	DATE	DWN	CHK		DESCRI	PTION		ECN FIN	ELECTRO TIN	DWG. NO.	186-cp48	31	INIT IN	ICH .	(4)	\exists	1	
	4 3						_	Δ .	2			i		1			•		
					1								'						