			4				3		7		2				1			.
•			ON THIS DRA NFIDENCE ANI			CELESTRA, IS D, USED OR			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	·
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					LB311243AP	_								
									260	300 kcmil	300 Navy	1/2	2.83	1.20	0.16	1.75	0.73	
_																		_
D	l N	IOTE:	1 ΔΙΙ	DIMENSION	JS ARE IN II	NCHES UNLESS	OTHERWISE											D
		IOTE.		CIFIED.	NO ARE IN II	NOTILS UNLLS	OTTIERWISE											
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE							⇒—B—⊸									
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	ł																	—
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								-80° x55									
	М	MATERIAL:	HIG	H CONDUC	TIVITY WRC	UGHT COPPER	2											
С	FI	INISH:		CTOR-TIN F		SS OTHERWIS	E		Beve	eled wire entr	y H							С
						FOR SILVER.												
										Wire inspection hole								
\rightarrow		INSTALLATION GUIDE								BOLT SIZE								
		DIE CODE = 66 DIE COLOR = White																
		()																
															Dia	alar		
В		⊢—G—⊶								Die Gold				В				
Ь									Color coded barrel markings—							ט		
	C UL US ROHS																	
		WIF	LISTED RE CONNECTORS VV/2/7/8-E513813		•													
	1																	
												EL FS	STRA	CO	RPO	RATIO	NC	
										HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.								
										www.huyaco.com Panyu Dist. Guangz								
Α										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
									+									
	00	29-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					٠	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECT							ROJECTION			
	REV		DWN	CHK		DESCRI		.	ECN FI	WROUGHT (DWG NO	243AP-26 186-cp48		INIIT	ICH	(1)	\exists	
			4	2	l		3	/	<u> </u>	2	YFLAIE	.50 op+0		111	1CH	Τ-		l
			-T		l		J	_	1	_			I		'			