		4		1		2		+	_	,		1		1			
	THE INFORMATION					3		V CELESTRA	2 WIRE		BOLT	A	В	С		ID	
	DISCLOSED IN COM DISLOSED EXCEP			REPRODUCE	D, USED OR			CAT.NO	CODE	FLEX 250 Navy 262.6	SIZE	±0.06	MIN	±0.04	R	±0.01	
								DA2514-252	250 kcmil	kcmil	1/4	2.16	0.78	1.17	1.38	0.63	
D	NOTE:	SPEC 2. ALL I	CIFIED. DA,DB,LA,LE	3,WP AND 、	NCHES UNLE	CAT.NO.S	ARE	Color coded marking Bolt Size									D
		ON C	ED BY "UND CODE WIRES FIX CAT.NO ERWISE SPI I "P".	S AND FLE:).WITH "L" I		DIE COLOR								_			
	MATERIAL:	HIGH	CONDUCT	IVITY WRO	UGHT COPP	PER				В							
С	FINISH:												С				
→	INSTALLATION GUIDE DIE CODE = 62 DIE COLOR = Yellow Inspection Hole																
В	C LISTE	D	A N	IEB:	_{\$} 3	oHs.	€	<u>□</u> †	Bevele	d entry			E	/			В
	WIRE CON	NECTOR															
																	
								CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
Α				_				WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								Α	
	00 23-Aug-25	Ruby Feng	Sinia Qiu	Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDU WROUGHT CO		14-252	S	CALE N7		RID ANGLE PE	ROJECTION	
1	REV DATE	DWN	CHK		DESC	CRIPTION		ECN	FINISH ELECTRO TIN I	PLATE DWG. NO. 1	86-cp04	84	nit IN	CH -	⊕ £		
		4				3		\triangle	2					1			