			4				3		∇			2					1					
•	DISCL	LOSED IN CON	NFIDENCE AND	NOT TO BE		F CELESTRA, IS ED, USED OR			CELES CAT.		CODE	IRE SIZE	v	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01			
	DISLC	SED EXCEPT	FOR WHICH	FURNISHED.					LB3138		CODE	313.1 kcmi										
									26	1	_	300 kg	cmil	3/8	1.83	1.55	0.19	1.00	0.86	1		
_																				l _		
D		NOTE:	1 11	DIMENSION	IC ADE IN I	NCHES LINI ES	S OTHER!	MISE												D		
		NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.						MOL														
						J SERIES OF C		r⇒ B → r														
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																				
_	┨	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.																				
		WITH "P".																				
	N	MATERIAL:	HIGI	H CONDUCT																		
С	C FINISH: ELECTOR-TIN PLATE UNLESS						SE		1	Beveled wire entry C										С		
	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.									21 11 12												
																	1					
		INSTALLATION GUIDE DIE CODE = 66 DIE COLOR = White									Wire inspection hole BOLT SIZE											
-	•																					
	•										Exp. C											
																	Diag	alar				
В												-G⊳) Bie C	0101		D		
Ь		c(UL)us Rohs,								Color coded barrel markings B												
		2002/95/EC																				
			WIRE CONF																			
	1																			-		
													C	FLFS	TRA	CO	RPO	RATIO	ON			
									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.									_				
									_	_ w	ww.huyad	co.com	Р	anyu D	ist. G	uangz	hou 5	11495.		1		
Α										TITLE WIRE CONNECTORS AND SOLDERING									Α			
											LUGS FOR CODE AND FLEX CABLE											
		00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION													
	REV	-	DWN	CHK			IPTION	miliaieu.	ECN	FINISH	WROUGHT	DW	LB31380			NIT IN	─ .	(1)	\exists			
	1 \ L V		4	OTTIN	<u> </u>	DLOCK	3				ELECTRO TII	N PLATE	18	86-cp484	<u> </u>	IN	СН 1		7	¹		
	•		4		1		J		4		۷						'					