	-																		
			4				3		\bigvee			2				1			,
•		NFORMATION LOSED IN CON				CELESTRA, IS D, USED OR				CELESTRA CAT.NO		RE SIZE	BOLT SIZE	B MIN	C C	D +0.015	G ±0.02	H ±0.01	'
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					l v	VP353801A-	CODE	FLEX							
										066	350 kcmil	350 Navy	3/8	1.79	1.29	0.18	1.00	0.80	
_																			_
D		IOTE:	1 11	DIMENSION	IC ADE IN II	NCHES UNLESS	OTHEDWI	CE.											D
		IOIE.		CIFIED.	NO ARE IN I	NCHES UNLES	OTHERWI	SE											
			2. ALL	DA,DB,LA,L	B,WP,AL,AS	S AND J SERIES		B											
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.						SE											
_	1																		
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.								D D									
			WIT	H "P".															
	N	MATERIAL:	HIG	H CONDUC	TIVITY WRO	OUGHT COPPER	R												
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE								Beveled wire entry————————————————————————————————————									
	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.									II									
										Wire inspection hole									
_	, IN	INSTALLATION GUIDE								BOLT SIZE									
		DIE CODE = 71 DIE COLOR = Red																	7
		DIE COLON = Neu									₹ + C								
												_							
D											₩-	-G-⊸				Die C	Olor		В
В										Color coded barrel markings—									
		C UL US ROHS																	
		WIR ZAD	ISTED E CONNECTORS		,														
	1																		
									Т				FIF	STRA	CO	RPO	RATIO	ON	
										HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.								_	
										www.huyaco.com Panyu Dist. Guangzhou 511495									
Α										WIRE CONNECTORS AND SOLDERING '									Α
											LUGS FOR CODE AND FLEX CABLE								
		00 16-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							-+	MAT	ERIAL HIGH-COND	ICTIVITY PRT. NO.		S	CALE	тні	RID ANGLE P	ROJECTION	
	00 REV		DWN	CHK		DESCR		ilialea.		ECN FINI	WROUGHT (OPPER WP35	3801A-06		INIIT	TS	6 (\Rightarrow	
	ΝΕV	DAIE	4	CHK	<u> </u>	DESCR	3			LUIN	electro tin	I PLATE	186-cp48	ეპ 	IN.	ICН 1	\$ 5		1
	-		4		I		J		4		۷					ı			