	i							I										
			4				3	4	7	2					1			
'			ON THIS DRA			CELESTRA, IS			CELESTRA		RE SIZE	BOLT	В	С	D	G	Н	'
			FOR WHICH		NEI NODOGE	D, COLD ON		-	CAT.NO LB351434A	CODE 350 kcmil	FLEX 350 Navy	+	MIN 1.93	±0.04	±0.015 0.18	±0.02 0.75	±0.01 0.84	l
								L	LD331434A	330 KUIIII	330 Navy	1/4	1.93	1.30	0.10	0.73	0.04	
																		l
D																		D
	N	OTE:		DIMENSION CIFIED.	IS ARE IN II	NCHES UNLES	SOTHERWISE											l
		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE									-	⊸ В						
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.						KE										
																		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																	l
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	I	IATERIAL:			TIVITY WRC	OUGHT COPPE	2											
								Beveled wire entry————————————————————————————————————										
С		FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							C									С
			SUF	FIX CAT.NO).WITH "SP"	FOR SILVER.												
										∕—Wire ir	spection hole							
									BOLT SIZE									
	INSTALLATION GUIDE DIE CODE = 71																	\leftarrow
		DIE COLOR = Red																
										⊸ (G⊸⊳				Die Col	lor		
В									Color coded barrel markings									В
	j																	
				ROHS 2002/95/EC	1													
		WIE ZM	LISTED RE CONNECTORS RVV/2/7/8.E513813		,													
	1																	
											7 A @ (CFI FS	TRΔ	COF	POF	2ΔΤΙΛ	N	
									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Towr									
										www.huyaco				ist. Guangzhou 511495.				
Α									TITLE WIRE CONNECTORS AND SOLDERING								Α	
									LUGS FOR CODE AND FLEX CABLE									
																D ANGLE PRO	DJECTION	
	00 14-Dec-25 Ruby Feng Sinia Qi				Celestra Standards Spec. Initialed. DESCRIPTION				WROUGHT COPPER LB351		351434A	1434A NTS			\bigcirc	THOSE TION		
1	REV	DATE	DWN	CHK		DESCR		A	ECN FIN	ELECTRO TIN I	PLATE DWG. NO.	186-cp485	5 "	INC		\(\psi\)	7	
			4				3	4	7	2					1			
								'										