			4				3		7		2				1				
I	DISCL	OSED IN CON	IFIDENCE AND) NOT TO BE F	PROERTY OF CEL REPRODUCED, US				CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01		
	DISLO	SED EXCEPT	FOR WHICH I	FURNISHED.]	-	LB353801AP 250		350 Navy	3/8	1.82	1.28	0.17	1.00	0.79		
D		IOTE:	1 411		IS ARE IN INCH			L				4	1				1	D	
		IOTE.		CIFIED.		ES UNLESS	OTHERWISE						_						
			LIST	ED BY "UND	B,WP AND J SE DERWRITERS II S AND FLEX/24	NC." AND "C	SA" FOR USE												
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								Ď - S ^S ^{×5}									
	M	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry H										
									Wire inspection hole										
\rightarrow	INSTALLATION GUIDE DIE CODE = 71																		
	DIE COLOR = Red																		
В									Color coded barrel markings										
																		—	
										HU	R								
										www.huyac		76. Hua Panyu I							
A									Intle WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								A		
	00		Ruby Feng	Sinia Qiu	Cele		ds Spec. Initialed			ATERIAL HIGH-CONDI WROUGHT (COPPER LB3538	01AP-25	50		TS				
	REV	DATE	DWN	СНК		DESCRI		٨			NPLATE	186-cp48	63 ^L	init IN	ICH	@ E]	
			4		I		3	4	7	2					1				