								ı										
			4				3	4	7	2					1			
•			ON THIS DRA			CELESTRA, IS			CELESTRA	<u> </u>	RE SIZE	BOLT	В	С	D	G	Н	1 '
			FOR WHICH		NEI NOBOOLI	5, 00EB OK			CAT.NO LB411243A	CODE 400 kcmil	FLEX 400 Navy		MIN 3.00	±0.04	±0.015	±0.02	±0.01 0.88	l
								l	LD411243A	400 KCIIIII	400 INAVY	1/2	3.00	1.41	0.17	1.73	0.00	ĺ
																		l
D																		D
	N <sup>(</sup>	OTE:		DIMENSION CIFIED.	IS ARE IN I	NCHES UNLES	SOTHERWISE											l
							.=					⊸—В		A .				l
		<ol> <li>ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.</li> </ol>																
																		l
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS									90° 55°								l
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																l	
	١ ,,	ATERIAL:				UGHT COPPE	2											l
									Beveled wire entry									
С		FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							´ → H → C									С
			SUF	FIX CAT.NO	.WITH "SP"	FOR SILVER.												
						—Wire inspection hole												
								BOLT SIZE										
$\rightarrow$		INSTALLATION GUIDE																
		DIE CODE = 76 DIE COLOR = Blue																7
		⊸_G_⊸									Die Co	nolo						
D									Color coded barrel markings									В
В								Color coded barrer markings									Ь	
		C (		RoHS 2002/95/EC	1													
		L WIR	LISTED RE CONNECTORS															
		ZM	VV/2/7/8.E513913															
_	1																	<b> </b>
												CELES	TDA				147	
										HUY								l
										76. Huancun Rd. Zhongcun Tow www.huyaco.com Panyu Dist. Guangzhou 511495.							1.	
Α									TITLE WIRE CONNECTORS AND SOLDERING								Α	
										LUGS FOR CODE AND FLEX CABLE								
		28-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				d.	WROUGHT COPPER LB411243A				NΤ	NTS THRID ANGLE PROJECTION						
ı	REV	DATE	DWN	CHK		DESCR		_	ECN FIN	ELECTRO TIN	PLATE DWG. NO.	186-cp489	6 UI	nit IN:	СН -	<b>⊕</b> Ł		
			4				3	4		2					1			
								I										