			4				3	4	7		2				1				
1	DISCL	OSED IN CON	IFIDENCE ANI) NOT TO BE F	PROERTY OF CELE REPRODUCED, USI	ESTRA, IS ED OR			CELESTRA CAT.NO	WI CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01		
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.]		LB411243A-250		400 Navy	1/2	3.00	1.39	0.18	1.75	0.86		
D	N	OTE:	1. ALL	DIMENSION	S ARE IN INCHE	ES UNLESS	OTHERWISE											D	
				CIFIED.								⊲[3						
			LIST	 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 															
			ON CODE WIRES AND FLEX/24 STRANDED CABLES.									n ^{**}		D				—	
			OTH		ECIFIED IN THE						_ 0 2								
	N	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER							Beveled wire entry										
С	F	INISH:			LATE UNLESS (E PER MIL - T - '		E		Bever	ed wire entry	H H	-						С	
					.WITH "SP" FOR														
										Wire i	nspection hol —BOLT SI								
\rightarrow	> INSTALLATION GUIDE																		
L	DIE CODE = 76 DIE COLOR = Blue																	7	
											G				Die C	olor			
В					\checkmark							coded ba	rrel ma	arkings				В	
U			C	Jus	RoHS									U				D	
			2800072178																
		I	1																
									┼──┤┃	HUY	R	76. Hua							
										www.huyac		Panyu							
A								LUGS FOR CODE AND FLEX CABLE									А		
	00 Rev	23-Aug-25 DATE	Ruby Feng	Sinia Qiu CHK	Celes	stra Standar DESCRII	ds Spec. Initialed	d.		WROUGHT C	DWG, NO.	11243A-25	0	INIT	TS .				
	REV	DATE	<u>4</u>			DESCKI	3	Δ		ELECTRO TIN	PLATE	186-cp48	99	IN	<u>сн</u> 1	Ψ			
			-		I		-	4		_			I						