	i						I											
		4				3	7	7	,	2				1				
ı				PROERTY OF CELEST REPRODUCED, USED				CELESTRA CAT.NO	•	RE SIZE	BOLT SIZE	B MIN	C .0.04	D	G	H	'	
		EXCEPT FOR WH						LB413801AF	CODE	FLEX	1		±0.04		±0.02	±0.01		
								260	400 kcmil	400 Navy	3/8	1.83	1.40	0.19	1.00	0.86		
D	NOTE	4	LL DIMENSIO	NO ADE IN INCLIES	LINII ECC OT	TIEDWICE											D	
	NOTE		SPECIFIED.	NS ARE IN INCHES														
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE							<b>В</b>									
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																	
	1																—	
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.							S S S									
	WITH "P".																	
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																	
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry————————————————————————————————————									С	
								71 11 17										
						Wire inspection hole												
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 76 DIE COLOR = Blue						BOLT SIZE											
										g c								
В			$\widehat{}$	<b>\</b>					-	-G⊸⊳l				) Die Ç	olor		В	
Ь	C(UL)US ROHS, Color coded barrel markings—							;/			Ь							
		,	ISTER	2002/95/EC														
			CONNECTORS //2/7/8.E513913															
	1																	
											ELES	STRA	CO	RPOI	RATIO	ON		
									HUY	A	76. Hua	ancun	Rd. Zł	nongci	ın Tow	_		
									www.huyac	o.com	Panyu I	Dist. G	Suangz	zhou 5	11495.			
Α								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									Α	
	00 01-Jul-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.																	
								N	IATERIAL <b>HIGH-COND</b> U	JCTIVITY PRT. NO.			CALE	THE	RID ANGLE P	ROJECTION		
		ATE DW	<del>-</del>	-	DESCRIPTI	<u> </u>		ECN F	WROUGHT C	5,000,000	301AP-26 186-cp49		INIT	TS .	<b>(</b> ) E	$\exists$		
	NEV D	4	,   01110	<u> </u>	3			\	2	PLATE	100-cp48	I O	11\	ICH   <b>1</b>	¥ -	7		
		4			3		4		۷			I		'				