		4			3			√ 2			1							
ļ			ON THIS DRA			F CELESTRA, IS			CELESTRA	·	RE SIZE	BOLT	В	С	D	G	Н	1 '
			T FOR WHICH		KLFKODOC	LD, OSLD OK			CAT.NO DB511243/	CODE	FLEX	SIZE 1/2	3.00		±0.015 0.22	±0.02	±0.01 0.99	ł
D	N	OTE:		DIMENSION CIFIED.	IS ARE IN	INCHES UNLE	SS OTHERWIS	E	DB3112437	A 500 kcmil	500 Navy	1/2	3.00		0.22	1.75	0.99	D
_			LIST ON (PRE OTH WIT	ED BY "UNE CODE WIRE -FIX CAT.NO IERWISE SP H "P".	DERWRITE S AND FLI D.WITH "L' PECIFIED I	ERS INC." AND EX/24 STRAND HAS NOT PE N THE SUFFIX	EP HOLE UNLE OF THE CAT.N	8° ×°									_	
		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER								Beveled wire entry								
С	F	INISH:	SPE	CIFED PLAT	E PER MI	.ESS OTHERW L - T -16366. " FOR SILVER					′ ⊸ H l∞	-						С
		/—Wire inspection hole																
-	D	INSTALLATION GUIDE DIE CODE = 87 DIE COLOR = Brown							BOLT SIZE									\leftarrow
В			c (U	Jus	Roh	IS VEC			Color coded barrel markings									В
			WIRE CONF															
																		_
									HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
А										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	00	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				ialed.	N	MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER DB511			1243A SCALE NTS			D ANGLE PR	PROJECTION			
	REV		DWN	CHK			RIPTION		ECN F	FINISH ELECTRO TIN	DWG NO	186-cp49	14	JNIT INC	- $+$	$\bigoplus $ \in	\exists	
		1	4				3		1	2	1	, -		0	1	-		¹
									I									