							1												
		4		3	2				1										
l				PROERTY OF CELES			CELEST		WIRE S		BOLT	В	С	D	G	Н			
		CEPT FOR WHICH		REPRODUCED, USEL	D OR		CAT.NO	<u>_</u>	CODE	FLEX	SIZE	MIN			±0.02	±0.01			
D							DB511434 <i>I</i>	(-250 50	0 kcmil	500 Navy	1/4	1.34	1.54	0.22	0.75	0.95	D		
	NOTE:		DIMENSION: ECIFIED.	S ARE IN INCHES	S UNLESS O					B	}								
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													D D					
	MATERIA	WIT	Ή "P".	ECIFIED IN THE S		ΓΗΕ CAT.NO.													
С	FINISH:	Ве	Beveled wire entry————————————————————————————————————																
				E PER MIL - T -16 WITH "SP" FOR S					–₩iro insp	action halo									
							Wire inspection hole —BOLT SIZE												
	DIE COD	INSTALLATION GUIDE DIE CODE = 87 DIE COLOR = Brown							Die Color										
В		C LIS		RoHS, 2002/95/EC		Color coded barrel markings													
																	_		
									UY,	4	ELES 76. Hua Panyu [ncun	Rd. Zh	ongcu	ın Tow				
Α				WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE															
	00 23-Aug	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE P WROUGHT COPPER DB511434A-250 NTS								OJECTION			
1	REV DAT		СНК		DESCRIPT	TION	ECN	FINISH	ECTRO TIN PLAT	51116 116	186-cp49		NIT INC	\dashv	+ E	\exists			
	1	4	,		(3	\triangle		2	•				1					