		4				3	7		,	2				1			
l	DISCLOSED	ATION ON THIS DR N CONFIDENCE AN KCEPT FOR WHICH	ID NOT TO BE				,	CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	· I
	DISLOSED E	CEPT FOR WHICE	T FORNISHED.					LB511434AP 250	500 kcmil	500 Navy	1/4	1.34	1.54	0.22	0.75	0.95	
D	NOTE:		_ DIMENSIOI ECIFIED.									D					
		2. ALI LIS	_ DA,DB,LA,L TED BY "UN	LB,WP AND J S DERWRITERS ES AND FLEX/	INC." AND "C	SA" FOR USE		B									
		OT WI	HERWISE SI TH "P".	PECIFIED IN T	HE SUFFIX O	HOLE UNLESS F THE CAT.NO.		D D									
С	MATER FINISH	ELE SP	ECTOR-TIN F	TIVITY WROU PLATE UNLES TE PER MIL - D.WITH "SP" F		Beveled wire entry H											
	INSTALLATION GUIDE DIE CODE = 87 DIE COLOR = Brown							Wire inspection hole BOLT SIZE									\leftarrow
В		c (U	D US TED	RoHS 2002/95/EC		Color coded barrel markings											
_			NECTORS /8.E513913														_
								HUYA® Www.huyaco.com CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
Α									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
	00 23-Au	g-25 Ruby Feno	Sinia Qiu	Ce	elestra Standa	rds Spec. Initialed.			ATERIAL HIGH-CONDU WROUGHT C	OPPER LB511	134AP-25 186-cp49	0	NIT	TS _	RID ANGLE PI	ROJECTION	
	INEV DE	4			DESCRI	3		<u> </u>	electro tin	PLATE	100-υμ49		IN	1 1		7	