		4 3			\vee	/ 2									.	
·	DISCLOSE	D IN CONFIDENC		HE PROERTY OF CELESTRA, BE REPRODUCED, USED OR	IS		ESTRA AT.NO	WI CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	Н ±0.01	
	DISLOSED	EXCEPT FOR W	HICH FURNISHE	D.		-	1434AP- 260	500 kcmil	500 Navy	1/4	1.39	1.55	0.23	0.75	0.95	
													1			
D	NOTE	:: 1.	ALL DIMENSI SPECIFIED.	ONS ARE IN INCHES UNI	ESS OTHERWISE											
		2.	LISTED BY "U	A,LB,WP AND J SERIES O INDERWRITERS INC." AN RES AND FLEX/24 STRAM												
				.NO.WITH "L" HAS NOT P SPECIFIED IN THE SUFF			D D									
	MATE	RIAL:	HIGH CONDL	ICTIVITY WROUGHT COF	PER											
С	FINIS	H:	ELECTOR-TIN PLATE UNLESS OTHERWISE Beveled wire entry SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.													С
	/—Wire inspection hole															
\rightarrow		INSTALLATION GUIDE						-BOLT SIZE								
		ODE = 87 OLOR = Brow	1				¢									7
В		C	(U) us		G→G Color coded barrel markings									В		
		LISTED														
			IRE CONNECTORS MVV/2/7/8.E513913													
																—
								HUY	R C				RPOI			
								ww.huyac					nongci zhou 5		n.	
А							TITLE WIRE CONNECTORS AND SOL					LDEF	RING	A		
						LUGS FOR CODE AND FLEX CA					CABL	E				
			Feng Sinia Qi		andards Spec. Initialed.			RIAL HIGH-CONDU WROUGHT C	OPPER LB5114	34AP-26	0		TS THE		ROJECTION	
I	REV D		VN CHK	DES	CRIPTION	EC	CN FINIS	ELECTRO TIN	PLATE DWG. NO. 1	86-cp49	41 U	nit IN	ICH - 1	Ψt		
		4		I	3	4		2					1			