			4				3				2		1		1			
I	DISCLO	DSED IN CON		NOT TO BE	PROERTY OF C REPRODUCED,				CELESTRA CAT.NO	W CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	'
]		LB513801AP- 263		535.3 kcmil 1325/24 (500 MCM NOM)	3/8	1.83	1.81	0.27	1.00	1.12	
D	N	OTE:		DIMENSION CIFIED.	NS ARE IN INC	HES UNLESS	OTHERWISE											D
			LIST	ED BY "UNI	DERWRITERS	SERIES OF CA 5 INC." AND "C 24 STRANDED	SA" FOR USE											
			OTH WITH	ERWISE SF H "P".	PECIFIED IN T	AS NOT PEEP HE SUFFIX OI		D D										
С		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry								
\rightarrow	INSTALLATION GUIDE DIE CODE = 87 DIE COLOR = Brown								-Wire inspection hole -BOLT SIZE									\Diamond
В				Dus	RoHS 2002/95/EC				K		G	led ba	rrel ma	ırkings	Die Ço	nolo		В
			LIS WIRE CONN ZMVV/2/7/8															_
										HU www.huyac		76. Hua	ancun	Rd. Zł		RATIC un Towi 11495.		
А									TITLE WIRE CONNECTORS AND SOLDERING A LUGS FOR CODE AND FLEX CABLE A									A
	00 REV	23-Aug-25 DATE	Ruby Feng	Sinia Qiu CHK	C	elestra Standar DESCRI	ds Spec. Initialed.			ATERIAL HIGH-COND WROUGHT (COPPER LB5138		3	CALE N	TS			
	KEV	DATE	4	UHK		DESCRI	3			ELECTRO TIN	NPLATE 1	86-cp49		IN	СН 1	¥ -	7	·