									1												
			4				3	7	\overline{V}		2				1						
'			ON THIS DRA			F CELESTRA, IS D. USED OR			CELESTR CAT.NO	• •	IRE SIZE	BOLT SIZE	B MIN	C	D	G ±0.02	H . 0 01	'			
			FOR WHICH								FLEX 1100/24 = 444			<u> </u>	1	1	±0.01				
									DB611243	A 600 kcmil	kcmil	1/2	3.00	1.75	0.24	1.75	1.08				
D	l																	D			
	l N	IOTE:		CIFIED.	IS ARE IN I	NCHES UNLESS	SOTHERWISE	:													
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE								⇒——B——⇒											
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																			
	l																				
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.									D D											
		WITH "P".																			
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																				
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE							Beveled wire entry									С			
				CIFED PLATED FIX CAT.NO		T -16366. ' FOR SILVER.			→ H H												
								∕─Wire inspection hole													
		INSTALLATION GUIDE								_BOLT SIZE											
	D	DIE CODE = 94																			
	"	DIE COLOR = Green																			
										→	-G⊳				Die	Color		_			
В	Color coded barrel markings—								s'		В										
		CUL)US ROHS																			
		L	ISTED SECONDECTORS)																
		ZM	VV/2/7/8.E513813																		
_	-																	—			
											_		TD		DDO	DATI	ONI				
										HUY		DELES					_				
										76. Huancun Rd. Zhongcun Towr www.huyaco.com Panyu Dist. Guangzhou 511495.											
Α									TITLE WIRE CONNECTORS AND SOLDERING							Α					
										LUGS FOR CODE AND FLEX CABLE											
		28-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					ıled.		WROUGHT	COPPER DB	311243A		N	TS TH	Φ -	ROJECTION	ECTION				
ı	REV	DATE	DWN	CHK		DESCR			ECN	FINISH ELECTRO TI	N PLATE DWG. NO.	186-cp49	57	INIT IN	ICH	₩ L					
			4				3		\triangle	2					1						
									I									- 			