		4		ı		3		7	•	2				1				
l	THE INFORMATION DISCLOSED IN CO	ONFIDENCE AND	NOT TO BE					CELESTRA CAT.NO	_	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01		
	DISLOSED EXCE	PI FOR WHICH	FURNISHED.			]		LB613801AP- 260	_	1100/24 = 444 kcmil	3/8	2.08	1.74	0.26	1.00	1.06		
D	NOTE:	1 All	DIMENSION	NS ARE IN INCI	HES LINII ESS	COTHEDWISE			•		•		•	•	•		D	
	NOTE.	SPE	CIFIED.						_									
		LIST	ED BY "UNI	B,WP AND J S DERWRITERS S AND FLEX/2	INC." AND "C		B V											
		ОТН		O.WITH "L" HA: PECIFIED IN TH			9° *5°											
	MATERIAL	HIGH	H CONDUC	TIVITY WROUG														
С	FINISH:	SPE	CIFED PLA	PLATE UNLESS TE PER MIL - T ).WITH "SP" FC	-16366.		Beveled wire entry————————————————————————————————————											
						Wire inspection hole												
$\rightarrow$		INSTALLATION GUIDE DIE CODE = 94							-BOLT SIZE									
	DIE COLOF	R = Green								C C				Dia Co				
В	C UL US ROHS.							Color coded barrel markings—									В	
		LIST WIRE CONN		2002/95/EC														
		ZMVV/2/7/8																
		1		I				1 1										
									HUY	A	<b>ELES</b> 76. Hua	incun	Rd. Zh	nongci	ın Tow			
А									www.huyac		Panyu Dist. Guangzhou 511495.					Α		
$\overline{}$							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE											
	00 23-Aug-2	5 Ruby Feng	Sinia Qiu	Ce	lestra Standar	rds Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER LB613801AP-260 NTS								ROJECTION		
ı	REV DATE	DWN	СНК		DESCRI			ECN FIN	ELECTRO TIN	DWG NO	186-cp49		NIT	CH	<b>(</b> ) [		l	
		4				3	4		2					1				