									I									
			4				3	7	$\overline{\vee}$		2				1			.
•			ON THIS DRA			F CELESTRA, IS ED, USED OR			CELESTRA CAT.NO		IRE SIZE	BOLT SIZE	B MIN	C	D	G ±0.02	H	· '
			FOR WHICH							CODE	FLEX 1325/24 = 535				1		±0.01	
									DB711221A-20	700 kcmil	kcmil	1/2	2.58	1.81	0.27	1.50	1.11	
D																		D
	N	IOTE:		DIMENSION CIFIED.	IS ARE IN I	INCHES UNLESS	OTHERWISE											
		 ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 									-	Е	3	~				
																		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								S & D									
										-90								
	M	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
0	l F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE							Beveled wire entry									
С			SPE	CIFED PLA	TE PER MIL	T -16366.	_		H -									С
			SUF	FIX CAT.NC	D.WITH "SP	" FOR SILVER.												
								∕—Wire inspection hole										
_										/—BOLT SIZE								
\rightarrow	INSTALLATION GUIDE DIE CODE = 99																	\leftarrow
	D	DIE COLOR =	= Pink								\$ C							
											-G				Die C	olor		
В	$ar{eta}$											В						
									Color coded barrel markings—									
		,	ISTER	2002/95/EC	1													
		WIR ZM	RE CONNECTORS IVV/2/7/8.E513813															
										ши		ELES	TRA	CO	RPO	RATIO	NC	
•								HUYA® CELESTRA CORPORATIO 76. Huancun Rd. Zhongcun Town							n.			
										www.huyaco.com Panyu l					Dist. Guangzhou 511495.			
Α										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								А
	00	00 16-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							М.		L HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION WROUGHT COPPER DB711221A-260 NTS							
•	REV	DATE	DWN	СНК		DESCR			ECN FII	VISH ELECTRO TIN	DWG NO	186-cp49		INIIT	ICH .	((
		1	4				3		<u> </u>	2		•	 		1	-		•
					ı				T				1					