									1									
			4				3	7	7		2				1			_
•			ON THIS DRA NFIDENCE ANI			F CELESTRA, IS D, USED OR			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D +0.015	G ±0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					WP711243A	1	1325/24 = 535					<u> </u>		
									043	700 kcmil	kcmil	1/2	2.80	1.79	0.27	1.75	1.11	1
_																		1_
D	l N	IOTE:	1 ΔΙΙ	DIMENSION	NS ARE IN I	NCHES UNLESS	CTHERWISE											D
	"	IOTE.		CIFIED.	NO ARE IIV I	NOTIES UNLES	OTTLKWISE											
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE							⊳——B——>									
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	ł																	
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								90° x5									
	M	MATERIAL:	HIG	H CONDUC	TIVITY WRO	OUGHT COPPER	?											
С	F	INISH:		CTOR-TIN F		ESS OTHERWIS	E		Beve	eled wire entr	y							С
						" FOR SILVER.												
										∕─Wire inspection hole								
\rightarrow		INSTALLATION GUIDE								BOLT SIZE								
		DIE CODE = 99 DIE COLOR = Pink																
															Die	alor		
В		G⊸G Color coded b													В			
Ь									Color coded barrel markings—									
	C US ROHS																	
		WIE ZM	.ISTED RE CONNECTORS VV/2/7/8.E513813															
	1																	_
												ELES	TRA	CO	RPO	RATIO	ON	
								HUYA® CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town.							_			
										www.huyac	ww.huyaco.com P		Panyu Dist. Guangzhou 511495.					
Α										WIRE CONNECTORS AND SOLDERING								Α
										LUGS FOR CODE AND FLEX CABLE								
	00	00 28-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.							М	ATERIAL HIGH-COND	UCTIVITY PRT. NO.	1243A-04	s S	CALE	TS THI	RID ANGLE PE	ROJECTION	
	REV		DWN	CHK		DESCRI		-	ECN FI	WROUGHT (DWG NO	1243A-04 186-cp49		NIIT	ICH	(E	\exists	
			4		l		3	/	1 - 3 - 1	2	TI ENTE	. 50 00 10	- 1	111	1	Т		'
			•		I		J	_	Ť	_			1					