								I										
			4				3	\downarrow			2				1			
ı						CELESTRA, IS			CELESTRA	WI	RE SIZE	BOLT	В	С	D	G	Н	. -
			FOR WHICH) NOT TO BE F FURNISHED.	REPRODUCEI	J, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	-	±0.015		±0.01	
D	NO [.]	TE:		DIMENSION CIFIED.	S ARE IN IN	NCHES UNLES	SS OTHERWISE	וטו	B811243A-260	800 kcmil	_	1/2	2.83	1.89	0.30	1.75	1.25	D
_			LIST ON 0 PRE OTH WITI	ED BY "UND CODE WIRE: -FIX CAT.NC IERWISE SP H "P".	DERWRITEF S AND FLE: D.WITH "L" I ECIFIED IN	RS INC." AND ' X/24 STRANDI HAS NOT PEE THE SUFFIX '	P HOLE UNLESS OF THE CAT.NO.		98° 55									
	MA ⁻	TERIAL:	HIGI	H CONDUCT	IVITY WRO	UGHT COPPE	ER .		Beveled wire entry									
С															С			
	/—Wire inspectio																	
\rightarrow	DIE	INSTALLATION GUIDE DIE CODE = 107 DIE COLOR = Orange							BOLT SIZE									
В			C U		RoH 2002/95/E	S					Color co	oded bar	rel ma	arkings-				В
										4U		DELES 76. Hua Panyu [incun	Rd. Zho	ongcu	n Towr		
Α									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									Α
	00 2	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					d.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER DB811243A-260 NTS							D ANGLE PRO	JECTION		
	REV	DATE	DWN	CHK		DESCF	RIPTION		ECN FINIS		DWG NO	186-cp50		INC	-+	$\bigoplus $ \in		
			4				3	4	'	2	1				1			