			4				3	\downarrow	7		2				1			
ı				WING IS THE D NOT TO BE F		CELESTRA, IS			CELESTRA		RE SIZE	BOLT	В	С	D	G	Н	
			T FOR WHICH		REPRODUCE	D, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	-	±0.015		±0.01	
D	N	IOTE:		DIMENSION CIFIED.	S ARE IN I	NCHES UNLES	SS OTHERWISE	<u> </u>	DB813801A-260	800 kcmil	_	3/8 E	1.83	1.95	0.30	1.00	1.25	D
			LIST ON (PRE OTH WIT	ED BY "UND CODE WIRE: FIX CAT.NO ERWISE SP H "P".	DERWRITE S AND FLE D.WITH "L" ECIFIED IN	RS INC." AND X/24 STRAND HAS NOT PEE I THE SUFFIX	P HOLE UNLESS OF THE CAT.NO.		D D									
	M	IATERIAL:	HIG	H CONDUCT	IVITY WRO	OUGHT COPPE		Beveled wire entry										
С	F	INISH:	SPE	CIFED PLAT	E PER MIL	ESS OTHERWI - T -16366. FOR SILVER.			2000.		′ ⊸ H ∞							С
										∕—Wire i	nspection hole							
-	D	INSTALLATION GUIDE DIE CODE = 107 DIE COLOR = Orange							BOLT SIZE									
В			C LIST		RoH 2002/95/	S					Color co	oded bar	rel ma	arkings –				В
										HU\ vww.huyac		DELES 76. Hua Panyu [incun	Rd. Zho	ongcu	n Towi		
Α								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					d.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER DB813801A-260 NTS THRID ANGLE PRO							OJECTION			
	REV		DWN	СНК			RIPTION		ECN FINI:		DWG NO	186-cp50		INC	-+	$\bigoplus \Box$	\exists	
			4				3	4	7	2	ı	-			1			