								1												
			4				3	7	7		2				1					
ı					PROERTY OF				CELESTRA		RE SIZE	BOLT	В	С	D	G	Н			
			FOR WHICH		REPRODUCED	, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01			
							_		DB911243A	900 kcmil	1925/24 = 777 kcmil	1/2	3.00	2.18	0.31	1.75	1.35			
								1			-	I		!				1		
D																		D		
2	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																			
	 ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 								B											
	ł																	—		
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".									જે _{, સ્} ૃ		D								
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																			
С	FI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry H									С		
	/—Wire inspection hole																			
_	INSTALLATION GUIDE								BOLT SIZE									1		
	DIE CODE = 115																			
	DIE COLOR = Yellow																			
												Dio C	alat							
В	G−⊖									/ Die Ç	.0101		В							
Ь									Color coded barrel markings—									Б		
	C US ROHS																			
	LISTED WHE CONNECTORS																			
		ZMN	VV/2/7/8.E513913																	
											_		TD 4			DATI	140			
	$\vdash \vdash$									HU		CELES 76. Hua								
				-						www.huyac	1	Panyu l								
Α																		Α		
				WIRE CONNECTORS AND SOLDERII																
										LUGS FOR CODE AND FLEX CABLE										
	00	16-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				l	MA	TERIAL HIGH-CONDI WROUGHT (COPPER DB	911243A	S	cale N	TS	RID ANGLE PI	ROJECTION	CTION				
	REV	DATE	DWN	CHK		DESCR	PTION		ECN FIN	ELECTRO TIN	I PLATE DWG. NO.	186-cp50	14	init In	ICH -	⊕ £		1		
			4				3	4		2					1					
					•			I					'							