			4				3		7		2			_	1			_
'			ON THIS DRA			CELESTRA, IS D. USED OR			CELESTRA CAT.NO	•	RE SIZE	BOLT SIZE	B MIN	C	D	G ±0.02	H ±0.01	·
			FOR WHICH							CODE	FLEX 1925/24 = 777							
									LB911243A	900 kcmil	kcmil	1/2	3.00	2.18	0.31	1.75	1.35	
D	l																	D
	l N	IOTE:		CIFIED.	IS ARE IN I	NCHES UNLESS	OTHERWISE											
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 							P B P									
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.								D D									
		WITH "P".																
	М	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE							Beveled wire entry									
		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								-> H								
							/— Wire inspection hole											
_		INSTALLATION GUIDE								BOLT SIZE								
	D	DIE CODE = 115																
	0	DIE COLOR = Yellow																
											<u></u>							
										∇-	-G				Die C	Color		_
В									Color coded barrel markings							В		
	CUL)US ROHS																	
		L	ISTED SECONDECTORS)													
		ZM	VV/2/7/8.E513913															
	-																	—
				<u> </u>							- A - C		TD			DATI	211	
										HU)		ELES					_	
										76. Huancun Rd. Zhongcun Tow www.huyaco.com Panyu Dist. Guangzhou 511495.						11.		
Α									-	WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								Α
																DO IDOTION	ION	
						Celestra Standards Spec. Initialed.			\perp	WROUGHT COPPER LB911243A				NTS A C				
1	REV	DATE	DWN	CHK		DESCRI			ECN F	ELECTRO TIN	DWG. NO.	186-cp50	16	INIT IN	ICH	Ψ -		
			4				3	_	1	2					1			
									I									