			4				3		7		2				1			.
•			ON THIS DRA NFIDENCE ANI			CELESTRA, IS D, USED OR			CELESTRA CAT.NO	CODE	RE SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D +0.015	G ±0.02	H ±0.01	·
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					LB113801AF									
									260	1000 KCMII	1000 Navy	3/8	2.08	2.19	0.33	1.00	1.34	
_																		_
D	l N	IOTE:	1 ΔΙΙ	DIMENSION	JS ARE IN IN	NCHES UNLESS	SOTHEDWISE											D
		IOTE.		CIFIED.	NO AILE IIV II	VOLIES ONLES	OTTLINWISE											
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE							B									
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.																
	ł																	—
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.																	
	WITH "P".																	
	М	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	FI	INISH:		CTOR-TIN F		SS OTHERWIS	E		Beve	eled wire entry	/ H							С
						FOR SILVER.												
										Wire inspection hole								
\rightarrow		INSTALLATION GUIDE								BOLT SIZE								
		DIE CODE = 125 DIE COLOR = White																
															Diac	alor		
В		⊲-G-∞) Die Colon								
Ь									Color coded barrel markings—								В	
	C US ROHS																	
		WIF	LISTED RE CONNECTORS VV/2/7/8-E513813		•													
	1																	
												ELES	STRA	CO	RPO	RATIO	NC	
										HUY		76. Hua					_	
										www.huyaco.com Panyu Dist. Guangzhou 511495.								
Α	\vdash									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								Α
									_									
	00	28-Oct-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					d	M	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJEC							ROJECTION		
	REV		DWN	CHK		DESCR		<u></u>	ECN FI	WROUGHT O	DWG NO	301AP-26 186-cp50		INIIT	ICH .	(\exists	
			4		l	2.20011	3	/		2	IFLAIE	.55 6656	I	111	1	Τ.		l
			T		I		J	_	Τ'	_			I		'			