		4		1	3		4	2	,				1			
I				 DERTY OF CELESTR <i>A</i> RODUCED, USED OF	A, IS		CELESTRA	WIRE	SIZE	BOLT	A	В	С	R	ID	
	DISLOSED EXCEP			NODOCED, OSED OF			CAT.NO LA2538P-251	CODE 250 kcmil	FLEX 250 kcmil 637/24	SIZE 5/8	±0.06	MIN 1.33	±0.04	2.59	±0.01	
							LA2550F-251	230 KCIIIII	Class I,K,M	3/6	2.14	1.33	1.29	2.39	0.70	
D	NOTE:		DIMENSIONS A	ARE IN INCHES UI	NLESS OTHER\	WISE	Color coded marking Bolt Size									D
_		LISTE ON C	ED BY "UNDER ODE WIRES A	/P,AL,AS AND J S RWRITERS INC." A ND FLEX/24 STR/ ITH "L" HAS NOT	AND "CSA" FOR ANDED CABLES	USE S.										
			ERWISE SPEC	IFIED IN THE SUF												
	MATERIAL:	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER B														
С	EN 1911													С		
-	DIE CODE =	INSTALLATION GUIDE DIE CODE = 62 DIE COLOR = Yellow						R Inspection Hole								
В	c ((Dus 🔩	A NEI	BS3 🐇	CE			Bevele	d entry			E				В
	LI WIR	STED E CONNECTOR														
									<u> </u>							
А							HUYA® Www.huyaco.com CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
		Ruby Feng			Standards Spec.	Initialed.		MATERIAL HIGH-CONDU WROUGHT CO	OPPER LA253	88P-251		CALE NT		ID ANGLE PR	OJECTION	
	REV DATE	4	CHK	DE I	SCRIPTION 3		ECN	ELECTROTIN	PLATE DWG. NO. 1	86-cp05	08 ^{UI}	IN(CH 1	Ψτ		
		4			3		4	۷					I			