							ı									
		4				3	\downarrow			2				1		
ı	THE INFORMATION ON THIS DE						·	CI	ELESTRA	Wire Size	•	Dii	mension (ir	n.)	Die Color] '
	DISCLOSED IN CO		REPRODUCED, US	DDUCED, USED OR				CAT.NO	Code		4	ID	OD		1	
								A	S4066-52	4/0 AWG	2.	73	0.55	0.88	White	1
6																
D																D
	NOTES:		SPECIFIED.		NCHES UNLI	ESS OTHERWISE										
			ALL DA,DB,L	ARE												
) "CSA" FOR USE										
	ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS															<u> </u> —
			OTHERWISE WITH "P".	SPECIFIED IN	N THE SUFFIX	K OF THE CAT.NO.										
	MATER			A110\/												
					LUMINIUM ALLOY					<u> </u>		.,1			MIZ.	
	FINISH:		ELECTRO TI	IN PLATE									Î			
С								#		⊕		#			 - 	С
										 -			Ţ ļ			
		ATION GUID	ÞΕ							+		7				
	DIE COL	DE = 66 .OR = White								٨						
_								~		Α		C>				
В																lв
D																
	1															 —
		1														
А											CI	ELES	STRA CORPO		RATION	
									HU'		70			ncun Rd. Zhongcun Tov		
									www.huya	aco.com	P			ıangzhou 511495.		
		 							TITLE WIRE	CONNECTORS AND SOLDERING				RING	A	
			-			LUGS FOR CODE AND FLEX CABLE										
												AINL]
	14-Dec-25	Hedy Xiao	Sinia Qiu						MATERIAL ALUMINIU		T. NO. AS40	66-52	SCAL	NTS TH	IRID ANGLE PROJECTION	
ı	REV DATE	DWN	CHK		DESCRIF	PTION		ECN	FINISH ELECTRO	TIN PLATE DV	VG. NG 186-0	1130451	64 UNIT	INCH	$\oplus \sqcup$	l .
		4				3	Δ		2				i			•
		-		ı			7		_				I			