| | | 4 | | | | 3 | + | 7 | | | 2 | | | | | 1 | |
|----------------|----------------------------------|------------------------------------|---|--|---|--|--------------------------------|-----------------|--------------------|-----------|---------|-----------|------------|--------------------|----------------|--------------------------------------|------------------|
| <u> </u> | | ONFIDENCE AN | D NOT TO BE I | PROERTY OF CEL REPRODUCED, US | | | CELESTRA CAT.NO AL103801 | Code 1/0 AWG | S | | :0.06 N | B (MIN ±0 | .04 ±0.015 | F ±0.02 0.38 | ±0.02 ±0 | 0.01 ±0.01 ±0 | H 0.02 .15 |
| D | NOTE: | SPE 2. ALL LIST ON PRE | CIFIED. DA,DB,LA,L ED BY "UNI CODE WIRE -FIX CAT.NO | IS ARE IN INCH B,WP AND J SE DERWRITERS II S AND FLEX/24 D.WITH "L" HAS PECIFIED IN THI | RIES OF CAT NC." AND "CS STRANDED NOT PEEP H | T.NO.S ARE BA" FOR USE CABLES. HOLE UNLES | s | O | - | | | | A — | | | - QO - | D |
| С | MATERIAL FINISH: | WIT : HIG ELE SPE | H "P". H CONDUCT CTOR-TIN P CIFED PLAT | FIVITY WROUGI LATE UNLESS TE PER MIL - T - WITH "SP" FOR | HT COPPER OTHERWISE 16366. | | | | ₹F | - - | — G - | _ | BOL | T SIZ | E H- | - | С |
| \rightarrow | INSTALLA DIE CODE DIE COLO | | | | | | | <u> </u> | - | - | — В | | | | V//// | | \leftarrow |
| OHS 2/95/EC | | | | | | | | | | | | | | | | | В |
| - | | | | | | | | | | | | | | | | | |
| | | | | | | | | | H | /.huya | CO.CO | ® m | 76. Hu | ancun | Rd. Zhon | PORATION ngcun Town. u 511495. | ١ |
| A | | | | | | | | | | | | | | | SOLD EX CAI | ERING BLE | A |
| | 00 31-Jul-2 | | | Cele | estra Standard | - | ed. | FON | MATERIAL FINISH | ALUMINIUN | М | PRT. NO. | AL103801 | | NTS | THRID ANGLE PROJE | CTION |
| | REV DATE | DWN 4 | CHK | | DESCRIP | 3 | 4 | ECN | | 2 | | | 186-cp51 | 89 | INCH | 1 | |