		Л	1	3	+		2					1			
l	THE INFORMATION	ON THIS DRAWING IS	THE PROERTY OF CELESTE D BE REPRODUCED, USED C	A, IS	CELESTRA	WIRE SIZE	BOLT	A	ВС		F .0.02	G	ID 10.01	H	l
		FOR WHICH FURNISH			CAT.NO AL403801	Code 4/0 AWG	SIZE 3/8		MIN ±0.4 1.93 1.2	_		±0.02	±0.01 0.60	±0.02	
D					Color coded barrel markings									D	
	NOTE:	 ALL DIMEN SPECIFIED 			BOLT SIZE										
			LA,LB,WP AND J SERIES			\int				-		OIZL			
			"UNDERWRITERS INC." VIRES AND FLEX/24 STF			HE COLOR									
			T.NO.WITH "L" HAS NO				当当	5	7	Ī	Ψ				
		WITH "P".	E SPECIFIED IN THE SU	FFIX OF THE CAT.NO).							<u> </u>			
	MATERIAL:	HIGH CONE	DUCTIVITY WROUGHT C	OPPER						G_		F			
С	FINISH:		IN PLATE UNLESS OTH PLATE PER MIL - T -1636						Δ	В					С
		SUFFIX CA	Γ.NO.WITH "SP" FOR SIL	VER.					,,						
								stic plug							
\rightarrow	INSTALLATIO						Bev	eled wire	entry						\leftarrow
	DIE CODE = DIE COLOR :					<u> </u>		7				0			7
						÷		# /				, <u>T</u>			
_								7 71⊥			1 1	J			_
В	.		/			Conductor Terr Compour	nination/ nd					ı			В
	C.	US RC	HS 195/EC												
	WIFE ZM	RE CONNECTORS IVV/2/1/8 E513913													
	-														
								A @	CFI	STD	A CO	RD∩E	ΣΔΤΙΛ)NI	
							JY.		76. H	luancur	n Rd. Zh	nongcu	ın Towr		
А				<u> </u>	www.huyaco.com Panyu Dist. Guangzhou 511495.								Α		
^					WIRE CONNECTORS AND SOLDERING										
					LUGS FOR CODE AND FLEX CABLE MATERIAL PRT. NO. SCALE THRID ANGLE P							DJECTION			
	00 03-Nov-25 REV DATE	Ruby Feng Sinia		Standards Spec. Initial ESCRIPTION			UMINIUM	DWG. N	AL40380		N.	TS 4	(\exists	
	INLV DAIL	4		3	\triangle		2		100-0		IN	СН (`	+ -	7	
		-	ı	-			_ -			I		·			