	_		4		1		3	+		2				1		1			
I	DISC		VFIDENCE AN	D NOT TO BE		OF CELESTRA, IS CED, USED OR		CELESTRA CAT.NO	WIRE SI Code	ZE BOLT	A ±0.06	B MIN	C ±0.04	D ±0.015	F ±0.02	G ±0.02	ID ±0.01	H ±0.02	
	DISEC	JSED EXCEPT	FOR WHICH	FURINISHED.				AL401243- 52	4/0 AW	G 1/2	5.78	3.38	1.19	0.33	0.63	1.75	0.55	1.80	
C	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. Color coded barrel markings —BOLT SIZE												D						
_	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																		
C	l _	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С					
+	Plastic plug INSTALLATION GUIDE DIE CODE = 66 DIE COLOR = White												\leftarrow						
В	Conductor Termination Compound Compound													В					
		2MA-V/2/7/8_E513813																	
								HUYA® Www.huyaco.com CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.											
Α								TITL	WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
		03-Nov-25					dards Spec. Initiale			MATERIAL PRT. NO. ALUMINIUM AI FINISH DWG. NO		AL401	401243-52 NTS			rs -	ID ANGLE PROJECTION		
	REV	DATE	DWN 4	CHK	<u> </u>	DESC	RIPTION 3		ECN FINI	2		^{′. ۱} 1	86-cp52	05 °	IN.	СН	Ψ -		
	-		-		I		-	7		_				I					