		4				3	+	7		2				1	
'	THE INFORMATION DISCLOSED IN CONTROL DISLOSED EXCE	ONFIDENCE ANI	O NOT TO BE I				CELESTRA CAT.NO AL511243	Code 500 kcmil	SIZE	±0.06	MIN ±0	C D ± 0.04 ± 0.015 ± 0.38 (		ID OD H ±0.01 ±0.01 ±0.0 0.90 1.28 2.66	_
D	NOTE:	SPE  2. ALL LIST ON PRE	CIFIED.  DA,DB,LA,L  ED BY "UNICODE WIRE  FIX CAT.NO	B,WP AND J S DERWRITERS S AND FLEX/2 D.WITH "L" HA	SERIES OF CA INC." AND "C 24 STRANDED S NOT PEEP	SA" FOR USE	s	) )				A —		- GO	D
С	MATERIAL: FINISH:	WIT HIGI ELE SPE	H "P". H CONDUCT CTOR-TIN P CIFED PLAT	FIVITY WROUG PLATE UNLESS FE PER MIL - 1 D.WITH "SP" FO	GHT COPPER S OTHERWISI T-16366.				-F-	- G		BOLT	SIZE H-		С
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 99 DIE COLOR = Pink														
HS Lighter															В
-		1	<u> </u>								<u> </u>	051 503	- DA COD	DODATION	_
							_		HU www.h	JY/	® om	76. Huan		PORATION ongcun Town. ou 511495.	A
A									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE						
	00 01-Jul-25 REV DATE	<del>                                     </del>	Sinia Qiu CHK	Се	elestra Standar	rds Spec. Initial	led.	ECN	MATERIAL ALL	MINIUM	PRT. NO.	AL511243	SCALE NTS	$\neg \bigcirc \neg$	NO
	NEV DAIL	4	OTIN		DESCRI	3	4			2	1	186-cp5229	INC	1	