	-		4		ı		3	4			2				1		1			
ı	DISCL		NFIDENCE AN	D NOT TO BE		OF CELESTRA, IS CED, USED OR		CELESTRA CAT.NO		SIZE	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	F ±0.02	G ±0.02	ID ±0.01	H ±0.02	
	DISEC	DSED EXCEPT	FOR WHICH	FURINISHED.				AL611243- 62	600	kcmil	1/2	6.55	3.15	1.96	0.52	0.63	1.75	0.92	2.47	
D	D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. Color coded barrel markings											-ROLT	C17E		D					
_	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.														—					
С	l _	WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С							
	INSTALLATION GUIDE DIE CODE = 106 DIE COLOR = Black																			
В	Conductor Termination Compound													В						
_	WIRE CONNECTORS ZMVV/27/da E513813																			
А										HUYA® 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.								_		
					WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE															
	00 REV	03-Nov-25	Ruby Feng	Sinia Qiu CHK			dards Spec. Initiale	ed.		MATERIAL ALI FINISH	ALUMINIUM		AL611	AL611243-62 NTS			ANGLE PE	PROJECTION		
	LKEV	DATE	4	CHK		DESC	3	<u></u>	CON		2		1	86-cp52	36	IN	CH 1	Ψ -	7	